

			1	
	Part Number:	rt Number:		4/10/2010
	TD1 42	205.2	CJ	4/10/2018
TP143		305-2	CHECKED	4/10/2019
			P.D.	4/10/2018
	Description:	anadu aar	APPROVED	4/10/2010
	Piezo Tra	ansuucer	C.E.	4/10/2018


This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


Top View


Side View


Bottom View

Recommended Land Pattern









Items	Specifications	Conditions							
Min. Sound Pressure Level	80	dB (@ 10cm)							
Resonant Frequency	3,300	Hz							
Rated Voltage	5	Vp-p							
Voltage Range	1 ~ 30	Vp-p		REVISION HISTORY					
Capacitance	15,000	pF	REV	DESCRIPTION	DATE	APPROVED			
Max. Rated Current	5	mA		Released from Engineering	4/10/2018	C.E.			
Storage Temperature	-30 ~ +80	°C		NOTES					
Operating Temperature	-20 ~ +70	°C		All dimensions are in mm unless otherwise noted					
Connection Method	Surface Mount Pads			2) All tolerances are ± 0.5 mm unless otherwise noted					
Mount Type	Surface Mount			3) All parts meet RoHS					
Housing Material	PPS			4) Subject to change or redrawn without notice					
Weight	2.3	g							
4 1 3 4 2 1 1									
Additional considerations can be found at www.dbunlimitedco.com/technical-articles.									