

| Specifications | | | Notes | | Revision History | | | | | |
|-----------------------|-----------|-------|--|------------------|------------------|---------------------------|------------|------------|-------------|------------|
| Description | Value | Unit | Notes | | Version | Description | | | Date | Approved |
| Technology | Piezo | | 1) All dimensions are in mm unless otherwise noted | | 1 | Released from Engineering | | | 10/21/2013 | J.S |
| Resonant Frequency | 4,000 | (Hz) | 2) All parts meet RoHS | | | | | | | |
| Rated Voltage | 12 | (V) | | | | | | | | |
| SPL @ 10cm | 80 | (dBA) | | | | | | | | |
| Tone | Single | | | | | | | | | |
| Mount Type | Thru-hole | | | | | | | | | |
| Voltage Range | 3~16 | (V) | | | | | | | | |
| Max Rated Current | 7 | (mA) | | | | | | | | |
| Housing Material | NORYL | | | | Drawn by | Date | Checked by | Date | Approved by | Date |
| Operating Temperature | -20 ~ +60 | °C | | | A.B. | 10/21/2013 | C.E. | 10/21/2013 | J.S | 10/21/2013 |
| Storage Temperature | -20 ~ +60 | °C | | Piezo Indicator | IP134012-1 | | | | | |
| Weight | 1 | (g) | | r iezo indicatoi | | 15104012-1 | | | | |

Additional considerations can be found at www.dbunlimitedco.com/technical-articles.